

Wood burning heater Harvia Pro 20 ES black

WKPR20ESM

Harvia 20 ES Pro is a popular choice for cottage saunas because of its practicality. The front of the heater has a fixed and easy-to-use 20-litre water tank, which heats the water at the same time as the heater heats up. The water tank has a tap on the side with a changeable handedness. The Pro model has a graphite black exterior, a stainless-steel front and a sturdy and impressive glass hatch to create cozy atmosphere to the sauna. Large stone capacity ensures excellent sauna baths.

Advantages

- Harvia 20 ES Pro with a front water tank is a practical heater for hot and dry sauna baths
- 20-litre water tank integrated on the front of the heater with a tap on the side
- Easy and safe to use
The front, top and ash box are made of stainless steel, which is easy to keep clean
- The cast iron glass hatch adds light and cozy atmosphere to the sauna
- Adjustable feet for easy installation



Features

Main material : Steel

H x W x D : 760.0 x 430.0 x 650.0 mm

Net weight (kg) : 65.0

Stone amount (kg) : 40.0

ID	GTIN	Power	Sauna room size min - max m3
WKPR20ESM	6417659036559	24.1 kW	8.0-20.0

Spare parts

Product	ID	Pcs
Outer casing Harvia 20 ES, painted	WX106	1
Adjustable legs for LG150/SL	SPZKIP-918	1
Nut R1/2 25mm	SPZES-250	1
Hinge pin, long	SP675	1
Extension 25 mm hot water faucet	SPZES-240	1
Water container 20 ES, stainless steel	SP035	1
Connection pipe 200 mm	SPZKIP-130	1
Gasket for hot water faucet	SPZES-260	1
Cast-iron grating 135x290mm, sauna heaters	SPZKIP-10	1
Ash box, 20 ES/SL,ESGF	SP681	1
Flue pipe connector	SPZROB-200	1
Cap for smoke hole (Ø 75 mm)	SPZROB-430	1
Cap for smoke hole (Ø 50 mm)	SPZKIP-170	1
Blocking plug with screws	SPZROB-190	1
Flue gas heat regulator 2 pcs	SP0009	1

Technical details

Technical data	Type / attribute	WKPR20ESM
	Color	Black
	Power output	24.1 kW
	Stone sizes	Ø10-15 cm
	Stone amount (kg)	40
Dimensions	Product width	430
	Product height	760
	Product depth (mm)	650
	Net weight (kg)	65
	Gross weight	67.5
Connections	Flue connection locations	Back, Top
	Chimney connection diameter	115
Safety and installation dimensions	Safety distance front (non-combustible materials)	300
	Safety distance front (combustible materials)	300
	Safety distance right side (combustible materials)	300
	Safety distance right side non-combustible materials	100
	Safety distance left side (combustible materials)	300
	Safety distance left side non-combustible materials	100
	Safety distance behind (non-combustible materials)	100
	Safety distance behind (combustible materials)	300
	Safety distance (Ceiling)	1300
	Room min. height(depends on connections and therefore from output, star/delta)	2090